Conference "Dynamic Wetting of Flexible, Adaptive, and Switchable Substrates"



Beitrag ID: 27 Typ: Talk

Droplet motion directed by reversible stiffness gradient on soft switchable surfaces

Dienstag, 9. November 2021 14:10 (20 Minuten)

Liquid droplet manipulation directed by stiffness gradient has been of great interest because of its numerous advantages in applications such as microfluidic systems (1), liquid collection (2), and tissue engineering (3-5). Patterning a stiffness gradient on the surface allows for moving of droplets towards the softer regions or create a well-known durotaxis effect and make them migrate to stiffer regions in a spatially controlled manner. In most systems, the stiffness gradient is patterned permanently and the effect is static so that the droplets move only in certain planned directions. Surfaces with switchable stiffness properties are of high interest to obtain an on-demand and reversible droplet manipulation. In this project, the lecithin-based photorheological fluids (6) based on spiropyran were modified to be employed as a photoswitchable soft surface. In these materials, a stiffness gradient can be created by light at arbitrary regions. Upon UV exposure, the viscosity and stiffness of the surface decrease more than 10- and 3-fold, respectively, which was confirmed by steady-state and dynamic rheological measurements. The properties alteration was due to the UV-induced structural changes of the material because of the photoswitching of spiropyran to merocyanine form. High resolution (7) and reversible stiffness gradient formation on this soft surface using a UV light provided us the opportunity to move the droplet on top of the surface towards softer areas without any stiffness patterning needed in advance. In the future, the concept will be used to manipulate droplets to coalescence and be taken from all over the surface.

References:

- 1. García S, Sunyer R, Olivares A, Noailly J, Atencia J, Trepat X. Generation of stable orthogonal gradients of chemical concentration and substrate stiffness in a microfluidic device. Lab Chip. 2015;15(12):2606–14.
- 2. Style RW, Che Y, Park SJ, Weon BM, Je JH, Hyland C, et al. Patterning droplets with durotaxis. Proc Natl Acad Sci U S A. 2013;110(31):12541–4.
- 3. Engler AJ, Sen S, Sweeney HL, Discher DE. Matrix Elasticity Directs Stem Cell Lineage Specification. Cell. 2006;126(4):677–89.
- 4. Dou J, Mao S, Li H, Lin JM. Combination Stiffness Gradient with Chemical Stimulation Directs Glioma Cell Migration on a Microfluidic Chip. Anal Chem. 2020;92(1):892–8.
- 5. Cheung YK, Azeloglu EU, Shiovitz DA, Costa KD, Seliktar D, Sia SK. Microscale Control of Stiffness in a Cell-Adhesive Substrate Using Microfluidics-Based Lithography. Angew Chemie. 2009;121(39):7324–8.
- 6. Lee HY, Diehn KK, Sun K, Chen T, Raghavan SR. Reversible photorheological fluids based on spiropyrandoped reverse micelles. J Am Chem Soc. 2011;133(22):8461–3.
- 7. Waldbaur A, Waterkotte B, Schmitz K, Rapp BE. Maskless projection lithography for the fast and flexible generation of grayscale protein patterns. Small. 2012;8(10):1570–8.

Hauptautoren: NEKOONAM, Niloofar (University of Freiburg, Department of Microsystems Engineering); Dr. HELMER, Dorothea (University of Freiburg, Department of Microsystems Engineering)

Vortragende(r): NEKOONAM, Niloofar (University of Freiburg, Department of Microsystems Engineering)

Sitzung Einordnung: Short talks